API Ballot 6580 TG DSE Page 1 of 1

Work Item Number	7066
Title of Work Item	Removal of clause 4.5
Ballot Revision Level	First
Type of Ballot (Initial, Comment, Comment resolution (reference API ballot#), 1 st Re-ballot, 2 nd Re-ballot, etc.)	Initial
Submitter Name(s)	Tony Collins
API Document Modified	Spec 7-1 second edition Drill Stem Elements
Impacted Documents	
Revision Key	Strike through

Work Item Charge: To delete clause 4.5

Ballot Rationale: Clause is redundant with chapter 10 of spec 7-2 which presents a risk of future conflict

Ballot Text: Ballot text attached

TG DSE Ballot item for WI 7066

Delete clause 4.5 of Spec 7-1 (which is redundant with section 10 of Spec 7-2)

4.5 Marking of Threaded-only Rotary Shouldered Connections (RSC)

When specified, for threaded-only RSCs used on products in accordance with this standard, the following shall be identified by stamping or stenciling the product adjacent to the connection with the following:

- a) threader's name or mark (optional),
- b) "API 7-2",
- c) THD,
- d) date of threading, and
- e) size and style of connection.

EXAMPLE—An NC46 connection would be marked: AB Co. (or mark), API 7-2, THD Mo [xx]-Yr [yy], NC46.

NOTE The connection marking may be applied to products, which are not covered by API standards if the threading and gauging stipulations in API 7-2 are met.